Installing the wheels

- Insert the axle through the wheel.
- Slide the washer over the axle pass the pin hole.
- Insert the axle and wheel through the frame. Slide the washer over the axle and insert the pin through the hole to firmly fasten the wheel assembly.




Installing the power cord arm




Installing the gun holder and tip holder

- Line up the screw sleeves with the holes in the upper handle
- Insert the screw and turn clockwise with a Phillips head screwdriver (not included) until the screw is tight.



Installing the upper handle

Push and hold the push-pin buttons on the sides of the upper handle assembly (1) as you slide the handle onto the frame (2).



Missing parts, accessories or need a service center?

Do Not Return to Store Call: 1-888-909-6757 www.GreenWorksTools.com



WARNING: This Quick Start Guide is not a substitute for reading the operator's manual. To reduce the risk of injury or death, user must read and understand operator's manual before using this product.

greenworks

1800 PSI / 1.1 GPM **ELECTRIC PRESSURE WASHER GPW 1800**

USING DETERGENT


- Put pressure washer detergent in detergent tank.
- Install blue or black soap nozzle.
- Squeeze trigger and wait approx.1 minute for soap.







SPRAY TIP	SPRAY TIP APPLICATION
 0'	Red - Stream tip (0°) ■ The red 0 degree tip provides a straight line of spray. It provides the highest amount of pressure. It is best used for removing hard, stuck-on grime or dirt.
W 25°	Green - Narrow fan tip (25°) ■ The green pressure washer tip provides high versatility with its 25 degree angle tip. Referred to as the washing tip, because it provides adequate pressure to remove dirt from surfaces, but is designed to not damage many surfaces. This pressure washer tip is designed for "sweeping" foliage or debris given its wide angle. This tip is versatile due to its wide area of cleaning and strong pressure application.
40°	White - Wide fan tip (40°) ■ The white 40 degree tip, referred to as the "fan" tip creates the widest area of cleaning with relatively low pressure. This pressure washer tip is best used for light or delicate cleaning applications. It is recommended for light cleaning on wood decks and other soft or delicate surfaces.
SOAP	Black - Soap spray tip ■ The black soap spray tip, is used for soap application. Soap is applied under low pressure high volume for optimum performance. Soap cannot be applied under high pressure with this machine.
	Turbo Nozzle Tip ■ The nozzle rotates in a zero to 15 degree spray pattern in a circular motion to break down tough dirt and grime. The spray pattern can cover area of 4 to 8 inches wide, depending on a distance between the tip and the surface being cleaned.



Set-up

Connect garden hose to pressure washer water intake



Assemble pressure washer gun to spray wand.



Connect desired pressure tip.



Insert high pressure hose into trigger handle.



Connect the high pressure hose to the water outlet connector.



Turn on water at outlet



Run water hose for 30 seconds with the motor in OFF position. This helps drain air from the tank and lines.



Connect power cord to wall outlet Extension cord not recommended.



Turn on Pressure Washer **IMPORTANT:** Ensure water outlet is On before turning power On to avoid damage to the pump.

NOTE:

released.

AUTO ON/OFF SWITCH: This Pressure washer is equipped with an Auto Start/Stop feature.

To operate: Turn the power switch to the On (I) position. Pump will pressurize and shut down immediately. Once the trigger of the gun is depressed the unit will turn on. Unit will shut off and be in standby mode when trigger is

